奇美實業股份有限公司

717010 台南市仁德區中正路一段 398 號 +886-6-266-3000 www.chimeicorp.com

CHIMEI CORPORATION

No. 398 , Sec. 1 , Zhongzheng Rd., Rende Dist., Tainan City 717010 , Taiwan

Low Residual Monomer SAN KIBISAN® PN-117H

L150FG

Product Description: High strength Chemcial resistant

ISO Test Method	Test Condition	Unit	PN-117H L150FG
1133	220°C×10KG	ml/10 min	8
1183	23 ℃	g/cm³	1.06
527	50 mm/min, yield	MPa	74
	50 mm/min, break	MPa	74
527	50 mm/min	%	6
- 178	2 mm/min	MPa	121
	2 mm/min	GPa	3.6
180/1A	23°C, Notched	KJ/m²	3
	-30°C, Notched	KJ/m²	_
179	23°C, Notched	KJ/m²	3
	Charpy '-30°C, Notched	KJ/m²	-
306	50°C/hr;1KG	°C	108
	50°C/hr;5KG	°C	104
75/A	1.8MPa, unannealed	°C	86
	1.8MPa, annealed	°C	104
11359	-	-	3.6~3.8*10-5
-	UL-94	-	1.5mm HB
294-4	-	%	0.2~0.7
1043	-	-	>SAN<
	1133 1183 527 527 - 178 180/1A 179 306 75/A 11359 - 294-4	1133 220°C×10KG 1183 23 °C 50 mm/min, yield 50 mm/min, break 527 50 mm/min 2 mm/min 30°C, Notched -30°C, Notched 23°C, Notched 50°C/hr;1KG 50°C/hr;1KG 50°C/hr;5KG 1.8MPa, unannealed 1.8MPa, annealed 11359 - UL-94 294-4 -	1133 220°C×10KG ml/10 min 1183 23 °C g/cm³ 50 mm/min, yield MPa 527 50 mm/min, break MPa 527 50 mm/min MPa 2 mm/min MPa 2 mm/min GPa 2 mm/min GPa 23°C, Notched KJ/m² -30°C, Notched KJ/m² Charpy '-30°C, Notched KJ/m² Charpy '-30°C, Notched KJ/m² 50°C/hr;1KG °C 50°C/hr;5KG °C 1.8MPa, unannealed °C 1.8MPa, annealed °C 1.1359 UL-94 - 294-4 - %

July 22, 2021

Notes: These are typical properties only and are not to be construed as specifications. Users should confirm results by their own test

The above statement is based on our current level of knowledge and covers the above products directly manufactured and supplied by CHI MEI CORPORATION at the date of issue. CHI MEI CORPORATION makes no warranties, whether express or implied, and assumes no liability in connection with any use of above information. Notwithstanding the foregoing, CHI MEI CORPORATION shall in no event be held obligated or liable for any claims due to or arising from (i) any customer provided, consigned, materials and/or parts, which are incorporated or adopted in the products; (ii) any combination of the products with material not provided or authorized by our company; (iii) any modifications to the products which are made or directed by customer; (iv) our compliance with the specifications, instructions, and/or designs provided by customer; (v) any anti-trust, unfair competition and/or other unlawful actions effected by customer; or (vi) any defects, infringement, breach and/or violation which are arising out of customer's faults or otherwise not solely and directly attributable to CHI MEI CORPORATION. In no event will CHI MEI CORPORATION be liable for any indirect, special, exemplary, punitive, or consequential damages (including lost profits) of any nature whatsoever whether arising out of the purchase, shipment, unloading, handling, or use of any product or otherwise.